


Product Information

Product Type: LIF Type
 Series: 4.8 (.187) Type Series
 Product Name: LIF1D-V9 MINI EGRI (A)_0.50-0.75
 Product Code: 0XXXX04469
 Tab Size: 4.8x0.50 mm
 Wire Size: 0.50-0.75 mm²



Product Codes

Product Code	Product Name	Approvals	Material	Plating	Maximum Temperature (°C)	Max. Contact Resistance with Min. Wire Size (mΩ)
0101104469-00	LIF1D-V9 MINI EGRI (A)_0.50-0.75 RPK	-	Brass	Pre-Tin	120 °C	0.75

*These values will be measured.

Insertion / Withdrawal Forces

1. Insertion (Max.): 25 N
 1. Withdrawal (Max.): 60 N
 1. Withdrawal (Min.): 20 N
 6. Withdrawal (Min.): 9 N

Crimp Pull-Out Force


	1. Pull Out Force	
	0.50 mm ²	0.75 mm ²
Min. Values	56 N Min.	84 N Min.

Current Carrying Capacity

Wire Section	Current Carrying Capacity max. A
0.50 mm ²	8
0.75 mm ²	10

Crimp Data*

Wire Size	Height (h) (mm)		Width (w) (mm)	
	Wire	Insulator	Wire	Insulator
0.50 mm ²	1.30 ±0.05	2.62 ±0.05	2.03 ±0.10	2.80 ±0.10
0.75 mm ²	1.40 ±0.05	2.97 ±0.05	2.04 ±0.10	2.80 ±0.10



*These values are valid with Hatko applicators and crimpers.

F05.067 REV.0