


### Product Information

Product Type: Straight  
 Series: End Multisplices 1.5 mm (.059) Series  
 Product Name: STK10KM  
 Product Code: 0XXXX10025  
 Wire Size: 0.50-1.00 mm<sup>2</sup>



### Product Codes

Product Code	Product Name	Approvals	Material	Plating	Maximum Temperature (°C)	Max. Contact Resistance with Min. Wire Size (mΩ)
0100110025	STK10KM RP	-	Brass	-	110 °C	-
0101110025	STK10KM RPK	-	Brass	Post-Tin	120 °C	-

### Insertion / Withdrawal Forces

1. Insertion (Max.): -  
 1. Withdrawal (Max.): -  
 1. Withdrawal (Min.): -  
 6. Withdrawal (Min.): -

### Crimp Pull-Out Force

	1. Pull Out Force		
	0.50 mm <sup>2</sup>	0.75 mm <sup>2</sup>	1.00 mm <sup>2</sup>
Min. Values	56 N Min.	84 N Min.	108 N Min.

### Current Carrying Capacity

Wire Section	Current Carrying Capacity max. A
0.50 mm <sup>2</sup>	8
0.75 mm <sup>2</sup>	11
1.00 mm <sup>2</sup>	15

### Crimp Data\*

Wire Size	Height (h) (mm)		Width (w) (mm)	
	Wire	Insulator	Wire	Insulator
0.50 mm <sup>2</sup>	1.35 ±0.05	-	2.00 ±0.10	-
0.75 mm <sup>2</sup>	1.41 ±0.05	-	2.00 ±0.10	-
1.00 mm <sup>2</sup>	1.54 ±0.05	-	2.00 ±0.10	-

\*These values are valid with Hatko applicators and crimpers.

F05.067 REV.0